



TILE SPECIFICATIONS

width 40mm LENGTH 60mm THICKNESS 1.6mm solid metal


GROUTLINE 1.32mm

40mm EE00



- Designed by Karim Rashid exclusively for ALLOY. One of eight innovative designs that play with the idea of pattern, grid, and repetition.
 A contemporary statement for interior and exterior applications.
- Immaculately designed and manufactured from solid, high quality metal to create an unsurpassed metal tile finish to last a lifetime. Will not dent, crack or de-laminate.
- Face mounted for ease of installation, to protect the metal tile face and keep tiles in formation. The ALLOY developed system includes 2 layers of protective adhesive tape and film on the tile face. No backing mesh is used. See the ALLOY Installation Guide for details.
- Designed and made in Australia for consistent high quality.
- Finishing pieces available to ensure the perfect installation where a full tile will not fit. ALLOY tiles are made from solid metal and have a specially chamfered edge, therefore tiles should not be cut on site.
- Grout not required unless installed in a wet area. It is essential that an un-sanded, non-grit grout is used, we recommend Laticrete 600/1600 series.
- Adhesive we recommend ALLOY One Pack Mastic (AOPM), available in black or white, specifically developed for ALLOY Tiles.
- Tile samples and AOPM can be ordered through alloydesign.com.au
- As a specialised metal tile, we recommend ALLOY tiles are installed by a highly experienced, professional tiler.

TILF SHEET



11.57 tile sheets per m²

FINISHING PIECE

Available on request

*NOT TO SCALE.

